

	SAFETY DATA SHEET	Version: R0001.0002
		Date of issue: 2017-02-20
	ACETONE	Revision date: 2017-02-20
		Change List:

Copyright 2015. LG Chem, Ltd. all rights reserved.

1. IDENTIFICATION**A. Product name**

- ACETONE

B. Recommended use and restriction on use

- General use : Not available
 - Restriction on use : Not available

C. Manufacturer / Supplier / Distributor information○ **Manufacturer information**

- Company name : LG Chem Ltd. Daesan Complex
 - Address : 54, Dokgot 1-ro, Daesan-eup, Seosan-city, Chungcheongnam-do, Korea
 - Dept. : BPA Production Team
 - Telephone number : 82-41-661-2900
 - Emergency telephone number : 82-41-661-2911
 - Fax number : 82-41-661-2789
 - E-mail address : lpchss@lgchem.com

○ **Supplier/Distributor information**

- Company name : LG Chem Ltd.
 - Address : 128, Yeoui-daero, Yeongdeungpo-gu, Seoul, Korea
 - Dept. : Olefins Sales Team
 - Telephone number : +82-2-3773-3934
 - Emergency telephone number : +82-2-3773-3456
 - Fax number : +82-2-3773-7758
 - E-mail address : lpcljm@lgchem.com

2. HAZARD IDENTIFICATION**A. GHS Classification**

- Flammable liquids : Category2
 - Serious eye damage/irritation : Category2A
 - Specific target organ toxicity(Single exposure) : Category3(Narcotic effects)
 - Specific target organ toxicity(Single exposure) : Category3(Respiratory tract irritation)
 - Aspiration hazard : Category2

B. GHS label elements○ **Hazard symbols**○ **Signal words**

- Danger

○ **Hazard statements**

- H225 Highly flammable liquid and vapour
 - H305 May be harmful if swallowed and enters airways
 - H319 Causes serious eye irritation
 - H335 May cause respiratory irritation.
 - H336 May cause drowsiness and dizziness.

○ **Precautionary statements**

1) Prevention

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools. Flammable liquids (chapter 2.6) 1, 2, 3
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P264 Wash hands thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.

2) Response

- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P331 Do NOT induce vomiting.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section MSDS 5).

3) Storage

- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

4) Disposal

- P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification : (NFPA Classification)

○ **NFPA grade (0 ~ 4 level)**

- Health : 1 , Flammability : 3, Reactivity : 0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
Acetone	Dimethyl ketone	67-64-1	99.97

4. FIRST AID MEASURES

A. Eye contact

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15minutes and call a doctor/physician.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Remove contact lenses if worn.

B. Skin contact

- Flush skin with plenty of wter for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.
- Get medical attention immediately.

C. Inhalation contact

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.

D. Ingestion contact

- About whether I should induce vomiting Take the advice of a doctor.
- Rinse your mouth with water immediately.
- Get medical attention immediately.
- If swallowed, large amounts of water to drink and do not induce vomiting.

E. Delayed and immediate effects and also chronic effects from short and long term exposure

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.

5. FIREFIGHTING MEASURES**A. Suitable (Unsuitable) extinguishing media**

- Dry chemical, carbon dioxide, regular foam extinguishing agent, spray
- Avoid use of water jet for extinguishing

B. Specific hazards arising from the chemical

- Not available

C. Special protective actions for firefighters

- Using a unattended and water devices in case of large fire and leave alone to burn if you do not imperative.
- Do not access if the tank on fire.
- Use appropriate extinguishing measure suitable for surrounding fire.
- Wear appropriate protective equipment.
- Keep containers cool with water spray.
- Vapor or gas is burned at distant ignition sources can be spread quickly.
- Due to the extremely low flash point, irrigating fire extinguishing may be less effective when put out a fire.

6. ACCIDENTAL RELEASE MEASURES**A. Personal precautions, protective equipment and emergency procedures**

- Ventilate closed spaces before entering.
- Do not touch spilled material. Stop leak if you can do it without risk.
- Move container to safe area from the leak area.
- Remove all sources of ignition.
- Do not direct water at spill or source of leak.
- Avoid skin contact and inhalation.

B. Environmental precautions

- Prevent runoff and contact with waterways, drains or sewers.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up

- Large spill : Stay upwind and keep out of low areas. Dike for later disposal.
- Notification to central government, local government. When emissions at least of the standard amount
- Dispose of waste in accordance with local regulation.
- Appropriate container for disposal of spilled material collected.
- Small leak: sand or other non-combustible material, please let use absorption.
- Wipe off the solvent.
- Dike for later disposal.
- Do not use plastic containers.

7. HANDLING AND STORAGE**A. Precautions for safe handling**

- Avoid direct physical contact.
- Since emptied containers retain product residue(vapor, liquid, solid) follow all MSDS and label warnings even after container is emptied.
- Avoid contact with incompatible materials.
- Refer to Engineering controls and personal protective equipment.
- Do not inhale the steam prolonged or repeated.
- Avoid contact with heat, sparks, flame or other ignition sources.

B. Conditions for safe storage, including any incompatibilities

- Save applicable laws and regulations.
- Do not apply any physical shock to container.
- Keep in the original container.
- Please pay attention to incompatibilities materials and conditions to avoid.
- Prevent static electricity and keep away from combustible materials or heat sources.
- Collected them in sealed containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits

- o **ACGIH TLV**
 - [Acetone] : TWA, 500 ppm(1188 mg/m³) STEL, 750 ppm (1782 mg/m³)
- o **OSHA PEL**
 - [Acetone]:1000ppm 2400mg/m³

B. Engineering controls

- A system of local and/or general exhaust is recommended to keep employee exposures above the Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. The use of local exhaust ventilation is recommended to control emissions near the source.

C. Individual protection measures, such as personal protective equipment

- o **Respiratory protection**
 - Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
 - Respiratory protection is ranked in order from minimum to maximum.
 - Consider warning properties before use.
 - Any chemical cartridge respirator with organic vapor cartridge(s).
 - Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
 - Any air-purifying respirator with a full facepiece and an organic vapor canister.
 - For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.
- o **Eye protection**
 - Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
 - Provide an emergency eye wash station and quick drench shower in the immediate work area.
- o **Hand protection**
 - Wear appropriate chemical resistant glove.
- o **Skin protection**
 - Wear appropriate chemical resistant protective clothing.
- o **Others**
 - Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance	
- Appearance	Liquid
- Color	Not available
B. Odor	Sweet Odor
C. Odor threshold	24-1615 mg/m ³
D. pH	Not available
E. Melting point/Freezing point	-94.6 °C

F. Initial Boiling Point/Boiling Ranges	56.1 °C
G. Flash point	-17 °C
H. Evaporation rate	Not available
I. Flammability(solid, gas)	Not available
J. Upper/Lower Flammability or explosive limits	13 / 2.2 %
K. Vapour pressure	24 kPa (20 °C)
L. Solubility	Not available
M. Vapour density	2
N. Specific gravity(Relative density)	0.8
O. Partition coefficient of n-octanol/water	-0.24
P. Autoignition temperature	465 °C
Q. Decomposition temperature	Not available
R. Viscosity	0.303 cP (25 °C 2))
S. Molecular weight	58.08

10. STABILITY AND REACTIVITY

A. Chemical Stability

- This material is stable under recommended storage and handling conditions.

B. Possibility of hazardous reactions

- Cylinders exposed to fire may vent and release flammable gas.

C. Conditions to avoid

- Avoid contact with incompatible materials and condition.
- Avoid : Accumulation of electrostatic charges, Heating, Flames and hot surfaces
- Avoid contact with heat, sparks, flame or other ignition sources.

D. Incompatible materials

- Not available

E. Hazardous decomposition products

- May emit flammable vapour if involved in fire.

11. TOXICOLOGICAL INFORMATION

A. Information on the likely routes of exposure

- (Respiratory tracts)
 - May be harmful if swallowed and enters airways
 - May cause respiratory irritation.
- (Oral)
 - Not available
- (Eye·Skin)
 - Causes serious eye irritation

B. Delayed and immediate effects and also chronic effects from short and long term exposure

- Acute toxicity
 - * Oral
 - [Acetone] : LD50 = 5280 mg/kg Rat (EHC(1990), SIDS(1997))
 - * Dermal
 - [Acetone] : LD50 = 12870 mg/kg rabbit (EHC(1990), PATTY(1994), SIDS(1997))
 - * Inhalation
 - [Acetone] : Steam LC50 = 76 mg/L/4hr Rat
- Skin corrosion/irritation
 - Not available
- Serious eye damage/irritation
 - Causes serious eye irritation
- Respiratory sensitization

- Not available
- **Skin sensitization**
 - Not available
- **Carcinogenicity**
 - * **IARC**
 - Not available
 - * **OSHA**
 - Not available
 - * **ACGIH**
 - [Acetone] : A4
 - * **NTP**
 - Not available
 - * **EU CLP**
 - Not available
- **Germ cell mutagenicity**
 - Not available
- **Reproductive toxicity**
 - Not available
- **STOT-single exposure**
 - May cause drowsiness and dizziness.
 - May cause respiratory irritation.
- **STOT-repeated exposure**
 - Not available
- **Aspiration hazard**
 - May be harmful if swallowed and enters airways

12. ECOLOGICAL INFORMATION

A. Ecotoxicity

- **Fish**
 - [Acetone] : LC50 >100 mg/l 96 hr Fathead minnows (NITE: EHC207, 1998)
- **Crustaceans**
 - Not available
- **Algae**
 - Not available

B. Persistence and degradability

- **Persistence**
 - Not available
- **Degradability**
 - Not available

C. Bioaccumulative potential

- **Bioaccumulative potential**
 - Not available
- **Biodegradation**
 - Not available

D. Mobility in soil

- Not available

E. Other adverse effects

- Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- Since more than two kinds of designaed waste is mixed, it is difficult to treat seperatly, then can be reduction or stabilization by incineration or similar process.

- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.

B. Special precautions for disposal

- The user of this product must disposal by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilities.
- Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG)

- 1090

B. Proper shipping name

- ACETONE

C. Hazard Class

- 3

D. IMDG Packing group

- II

E. Marine pollutant

- Not available
- Not applicable

F. Special precautions for user related to transport or transportation measures

- Local transport follows in accordance with Dangerous goods Safety Management Law.
- Package and transport follow in accordance with Department of Transportation (DOT) and other regulatory agency requirements.
- Air transport(LATA): Not subject to LATA regulations.
- EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- EmS SPILLAGE SCHEDULE : S-D (Flammable liquids)

15. REGULATORY INFORMATION

A. National and/or international regulatory information

- **POPs Management Law**
 - Not applicable
- **Information of EU Classification**
 - * **Classification**
 - [Acetone] : F; R11Xi; R36R66R67
 - * **Risk Phrases**
 - [Acetone] : R11, R36, R66, R67
 - * **Safety Phrase**
 - [Acetone] : S2, S9, S16, S26, S46
- **U.S. Federal regulations**
 - * **OSHA PROCESS SAFETY (29CFR1910.119)**
 - Not applicable
 - * **CERCLA Section 103 (40CFR302.4)**
 - [Acetone] : 2267.995 kg 5000 lb
 - * **EPCRA Section 302 (40CFR355.30)**
 - Not applicable
 - * **EPCRA Section 304 (40CFR355.40)**
 - Not applicable
 - * **EPCRA Section 313 (40CFR372.65)**
 - Not applicable
- **Rotterdam Convention listed ingredients**
 - Not applicable
- **Stockholm Convention listed ingredients**

- Not applicable
- **Montreal Protocol listed ingredients**
 - Not applicable

16. OTHER INFORMATION

A. Reference

- The information contained herein is believed to be accurate. It is provided independently of any sale of the product for purpose of hazard communication. It is not intended to constitute performance information concerning the product. No express warranty, or implied warranty of merchantability or fitness for a particular purpose is made with respect to the product or the information contained herein.
- This Safety Data Sheet was compiled with data and information from the following sources: KOSHA, NITE, ESIS, NLM, SIDS, IPCS

B. Issue date

- 2017-02-20

C. Revision number and Last date revised

- 1 times, 2017-02-20

D. Other

- This SDS is prepared according to the Globally Harmonized System (GHS).